

IN THE CLAIMS

1. (Previously Presented) A method for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the method comprising the steps of:

decrypting at least a section of a file with a first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;

determining if there are any updates in the section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates then performing the steps of:

decrypting, with the first decrypting key, a reference table containing one or more location indicators for storing the data items in a data table; and

populating the data table with the data items at locations specified by the location indicators in the reference table.

2. (Original) The method according to claim 1, wherein the step of populating the data table includes populating the data table in a tamper resistant environment.

3. (Previously Presented) The method according to claim 1, further comprising the steps of retrieving from a key database at least one of:

a base key;
a time-stamp; and
an update number.

4. (Previously Presented) The method according to claim 1, wherein the step of determining if there are any updates in the section of the file includes;

getting an offset to an update reference table;

SOM920010003US1

2 of 15

09/884,618

decrypting the update reference table containing one or more ~~data table~~ location indicators for updates to the data items with the first decrypting key; and
populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

5. (Withdrawn) A method for storing electronic digital content, the content containing an index to memory address locations containing one or more members forming the library, the library index stored in a data table in memory, the data table comprising one or more entries with address references to metadata and address references to content data for each of the one or more members forming the library, the method comprising the steps of:

writing a header section comprising a row/size indicator;

writing a data section immediately after the header section, the data section comprising one or more data items represented in a length-data string format, wherein the data section comprises references to one or more pieces of metadata and content data forming the one or more members in the library of electronic digital content;

writing a reference table section immediately after the data section, the reference table section comprising a plurality of row/column entries, wherein a number of columns forming each row is specified by the row/size indicator and wherein one or more row/column entries in each row of the reference table represent offsets to each of the one or more pieces of metadata and content data forming the electronic digital content; and

writing a trailer section immediately after the reference table section, the trailer section comprising an offset to the beginning of the reference table.

6. (Withdrawn) The method according to claim 5, wherein the step of writing the reference table section includes writing a reference table section with a token identifier to be determined subsequently if the stored library was altered by an unauthorized party.

7. (Withdrawn) The method according to claim 5, wherein the step of writing the data section immediately after the header section includes writing the data section within a tamper resistant environment.

8. (Withdrawn) The method according to claim 6, further comprising the step of encrypting the data section with a first encrypting key.

9. (Withdrawn) The method according to claim 7, wherein the step of writing a reference table section further comprises writing one or more update content sections representing one or more updates to the one or more members forming the library of electronic digital content, wherein each of the one or more update content sections is written after the trailer section, and wherein each update content section includes at least one:

update data section, the update data section comprising one or more updated data items represented in a length-data string format wherein the data section comprises references to one or more pieces of updated metadata and updated content data forming the electronic digital content;

update reference table section immediately after the update data section, the update reference table section comprising row/column entries, wherein one or more row/column entries in each row of the reference table represent offsets to each of the one or more pieces of metadata and content data forming the electronic digital content; and

update trailer section immediately after the update reference table section, the update trailer section comprising an offset to the beginning of the update 1 reference table.

10. (Previously Presented) A method for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the method comprising the steps of:

decrypting a trailer section of a file with a first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the trailer section of the file;

determining if there are any updates in the trailer section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates then performing the steps of:

decrypting, with the first decrypting key, a reference table containing one or more location indicators for storing the data items in a data table;

decrypting ~~one of~~ the data items with the first decrypting key; and

populating the data table with the data items at locations specified by the location indicators in the reference table ~~with data~~.

11. (Previously Presented) A computer readable medium containing programming instruction for forming a data table stored in memory, the data table forming a library index of storage locations to electronic digital content, the programming instructions comprising:

decrypting at least a section of a file with a first decrypting key, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;

determining if there are any updates in the section of the file to any data items that form a library index of storage locations to electronic digital content and if there are no updates-then performing the steps of:

decrypting, with the first decrypting key, a reference table containing one or more location indicators for storing the data items in a data table; and

populating the data table with the data items at locations specified by the location indicators in the reference table.

12. (Original) The computer readable medium according to claim 11, wherein the programming instruction of populating the data table includes populating the data table in a tamper resistant environment.

13. (Previously Presented) The computer readable medium according to claim 11, further comprising the programming instruction of retrieving from a key database at least one of:

- a base key;
- a time-stamp; and
- an update number.

14. (Previously Presented) The computer readable medium according to claim 11, wherein the programming instruction of determining if there are any updates in the section of the file includes:

- getting an offset to an update reference table;
- decrypting the update reference table containing one or more location indicators for updates to the data items with the first decrypting key; and
- populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

15. (Previously Presented) An end user information processing system comprising:

- a data table stored in memory, the data table forming a library index of storage locations to electronic digital content;
- a first decrypting key for decrypting at least a section of a file, wherein the first decrypting key is formed as a combination of a base key, a time-stamp, and an update number so as to uniquely correspond to both a given time and a given update in the section of the file;

means for determining if there are any updates in the section of the file to one or more data items that form the library index of storage locations to electronic digital content and if there are no updates then

decrypting, with the first decrypting key, a reference table containing one or more location indicators for storing the data items in a data table; and

populating the data table with the data items at locations specified by the location indicators in the reference table ~~with data~~.

16. (Previously Presented) The end user information processing system according to claim 15, wherein the means for populating the data table includes populating the data table in a tamper resistant environment.

17. (Previously Presented) The method according to claim 1, further comprising decrypting one or data items with the first decrypting key.

18. (Previously Presented) The method according to claim 4, further comprising decrypting the updates to the data items with the first decrypting key.

19. (Previously Presented) The computer readable medium according to claim 11, further comprising decrypting one or data items with the first decrypting key.

20. (Previously Presented) The end user information processing system according to claim 15, further comprising decrypting the updates to the data items with the first decrypting key.

21. (Previously Presented) The end user information processing system according to claim 15, wherein the means for populating further comprises
getting an offset to an update reference table;

decrypting the update reference table containing one or more location indicators for updates to the data items with the first decrypting key; and;
populating the data table with the updates to the data items at locations specified in the update reference table with the updates to the data items.

22. (Previously Presented) The end user information processing system according to claim 20, further comprising decrypting the updates to the data items with the first decrypting key.

SOM920010003US1

8 of 15

09/884,618